

Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx Weight (g)	Internal Impedance (mΩ)	Cut-off Voltage (V)
			T ±0.2 mm	W ±0.5 mm	L ±1.0 mm			
SDL4012 20	60	3.7	4.0	12	20	1.8	≤600	2.75V
SDL4513 21	75	3.7	4.7	13	22	2.0	≤380	2.75V
SDL4020 19	120	3.7	4.0	20	21	2.8	≤300	2.75V
SDL5511 32	140	3.7	≤5.7	11	32	3.1	≤200	2.75V
SDL4020 25	150	3.7	4.0	20	25	3.4	≤180	2.75V
SDL3524 26	180	3.7	3.5	24	26	4	≤150	2.75V
SDL4520 30	200	3.7	4.0	20	30	4.6	≤250	2.75V
SDL6015 28	200	3.7	6.0	15	28	4.5	≤180	2.75V
SDL4015 45	220	3.7	4.0	15	45	4.8	≤165	2.75V
SDL6017 30	220	3.7	6.0	17	30	4.9	≤165	2.75V
SDL6020 25	240	3.7	6.0	20	25	5.1	≤120	2.75V
SDL5020 30	250	3.7	5.0	20	30	5.3	≤150	2.75V
SDL4515 43	260	3.7	4.5	15	43	5.3	≤120	2.75V
SDL4520 36	270	3.7	4.5	20	36	5.9	≤130	2.75V
SDL6024 25	300	3.7	6.0	24	25	6.2	≤120	2.75V
SDL5024 35	350	3.7	≤5.2	24	35	7.4	≤100	2.75V
SDL5012 71	390	3.7	5.0	12	71	8.0	≤100	2.75V
SDL3025 62	400	3.7	3.0	25	62	9.2	≤100	2.75V
SDL5522 40	400	3.7	5.5	22	40	8.2	≤100	2.75V
SDL6520	400	3.7	≤6.5	20	35	7.7	≤100	2.75V

35								
SDL6512 60	400	3.7	≤6.7	12	61	9.5	≤80	2.75V
SDL5430 33	450	3.7	5.4	30	33	9.0	≤95	2.75V
SDL7525 30	450	3.7	≤7.5	25	30	9.0	≤80	2.75V
SDL9025 30	600	3.7	9.0	25	30	14	≤70	2.75V
SDL4530 48	600	3.7	4.5	30	48	14.0	≤80	2.75V
SDL7515 57	650	3.7	7.5	15	57	14.5	≤70	2.75V
SDL6023 51	650	3.7	6.0	23	51	14.0	≤75	2.75V
SDL5030 46	700	3.7	5.2	30	46	14	≤55	2.75V
SDL8030 33	730	3.7	8.0	30	33	15	≤60	2.75V
SDL5524 56	750	3.7	5.7	24	56	15	≤55	2.75V
SDL5034 48	800	3.7	5.0	34	48	17	≤65	2.75V
SDL5830 48	800	3.7	≤5.8	30	48	17	≤55	2.75V
SDL5034 50	850	3.7	5.0	34	50	18	≤60	2.75V
SDL6030 48	850	3.7	≤6.0	30	48	18	≤50	2.75V
SDL3842 56	900	3.7	4.0	42	58	20	≤50	2.75V
SDL8230 38	900	3.7	≤8.5	30	38	19	≤50	2.75V
SDL6530 46	900	3.7	6.5	30	46	19	≤60	2.75V
SDL5530 55	1000	3.7	≤6.2	30	55	20	≤50	2.75V
SDL6034 50	1000	3.7	6.0	34	50	21	≤60	2.75V
SDL7030 48	1000	3.7	7.2	30	48	21	≤55	2.75V
SDL3050 69	1000	3.7	3.0	50	69	20	≤50	2.75V

SDL7530 48	1100	3.7	7.5	30	48	20	≤55	2.75V
SDL7032 55	1200	3.7	7.0	32	55	22	≤45	2.75V
SDL5023 104	1200	3.7	5.0	23	104	24	≤55	2.75V
SDL6336 50	1200	3.7	≤6.5	36	50	22	≤50	2.75V
SDL3047 82	1300	3.7	≤3.5	47	82	26	≤40	2.75V
SDL6035 62	1300	3.7	≤6.2	35	62	26	≤40	2.75V
SDL3550 69	1350	3.7	≤3.7	50	69	26	≤40	2.75V
SDL7536 50	1400	3.7	≤7.7	36	50	27	≤50	2.75V
SDL8034 48	1400	3.7	8.0	34	48	26	≤45	2.75V
SDL9530 48	1420	3.7	9.5	30	48	27	≤40	2.75V
SDL4238 85	1450	3.7	≤4.5	38	85	28	≤40	2.75V
SDL6020 120	1450	3.7	6.0	20	120	27	≤40	2.75V
SDL9634 48	1500	3.7	9.2	34	48	30	≤25	2.75V
SDL8036 52	1500	3.7	8.0	36	52	31	≤40	2.75V
SDL4645 66	1500	3.7	4.6	45	66	29	≤40	2.75V
SDL9523 62	1500	3.7	10.5	23	62	28	≤50	2.75V
SDL1030 48	1500	3.7	≤10. 2	30	49	28	≤40	2.75V
SDL7035 62	1600	3.7	7.2	35	62	31	≤35	2.75V
SDL8336 52	1650	3.7	8.3	36	52	31	≤40	2.75V
SDL6242 58	1650	3.7	6.2	42	58	31	≤35	2.75V
SDL4040 104	1650	3.7	4.0	40	104	34	≤35	2.75V
SDL9534 50	1700	3.7	9.5	34	50	34	≤40	2.75V

SDL1037 46	1750	3.7	≤10	37	46	35	≤40	2.75V
SDL4528 135	1800	3.7	≤4.5	28	135	36	≤40	2.75V
SDL4548 84	1800	3.7	≤4.8	48	84	36	≤35	2.75V
SDL5054 68	1800	3.7	5.0	54	68	34	≤35	2.75V
SDL1034 50	1800	3.7	≤10. 2	34	50	32	≤40	2.75V
SDL8535 62	2000	3.7	8.7	35	62	40	≤40	2.75V
SDL4045 100	2000	3.7	≤4.2	45	100	40	≤25	2.75V
SDL5550 69	2000	3.7	≤5.7	50	69	40	≤40	2.75V
SDL6232 96	2000	3.7	6.2	32	96	40	≤40	2.75V
SDL4550 95	2000	3.7	4.5	50	95	40	≤40	2.75V
SDL5048 84	2100	3.7	≤5	48	84	41	≤25	2.75V
SDL5528 135	2200	3.7	≤5.8	28	135	43	≤40	2.75V
SDL8530 80	2200	3.7	8.5	30	80	42	≤26	2.75V
SDL6850 60	2350	3.7	6.8	50	60	44	≤20	2.75V
SDL6838 85	2400	3.7	≤6.8	38	85	44	≤30	2.75V
SDL5548 84	2500	3.7	≤5.7	48	84	46	≤25	2.75V
SDL8230 90	2600	3.7	≤8.3	30	90	48	≤18	2.75V
SDL8050 60	2700	3.7	8.0	50	60	51	≤15	2.75V
SDL9544 60	2900	3.7	9.5	44	60	53	≤15	2.75V
SDL6548 84	3000	3.7	≤6.7	48	84	57	≤16	2.75V
SDL4048 135	3000	3.7	≤4.2	48	135	57	≤20	2.75V
SDL6834 125	3000	3.7	6.8	34	125	57	≤20	2.75V

SDL5056 90	3100	3.7	5.0	56	90	56	≤20	2.75V
SDL5056 90	3100	3.7	5.3	56	90	56	≤15	2.75V
SDL5556 90	3200	3.7	5.5	56	90	57	≤20	2.75V
SDL8542 84	3200	3.7	8.5	42	84	57	≤20	2.75V
SDL6055 85	3200	3.7	6.0	55	85	60	≤12	2.75V
SDL6045 100	3300	3.7	≤6.2	45	100	61	≤14	2.75V
SDL5054 97	3300	3.7	5.2	54	97	59	≤13	2.75V
SDL7042 95	3400	3.7	7.0	42	95	61	≤10	2.75V
SDL4867 102	3400	3.7	4.8	67	102	68	≤10	2.75V
SDL7045 100	3600	3.7	≤7.0	45	100	65	≤15	2.75V
SDL8248 84	4000	3.7	≤8.5	48	84	73	≤13	2.75V
SDL6443 128	4000	3.7	6.5	43	128	71	≤9	2.75V
SDL7055 85	4000	3.7	7.2	55	85	73	≤10	2.75V
SDL5548 135	4200	3.7	≤5.7	48	135	77	≤10	2.75V
SDL8050 95	4500	3.7	≤8.2	50	95	83	≤9	2.75V
SDL8065 80	5000	3.7	≤8.3	65	80	90	≤8	2.75V
SDL7543 128	5000	3.7	7.5	43	128	95	≤9	2.75V
SDL8574 135	10000	3.7	8.7	74	135	165	≤5	2.75V